

READY MIX -36°C

HIGH PERFORMANCE COOLANT

READY MIX IS A HIGH-PERFORMANCE COOLANT DESIGNED TO PROVIDE EFFICIENT PROTECTION DOWN TO -36°C DURING WINTER CONDITION.

IT IS A READY TO USE PRODUCT THAT HAS BEEN PREMIXED WITH 50% KINSLEE ANTIFREEZE AND 50% WATER.

FEATURES & BENEFITS

READY MIX CONTAINS MONO ETHYLENE GLYCOL AND HELPS TO PREVENT WINTER FREEZING AND SUMMER OVERHEATING OVER A 2 YEARS PERIOD.

IT ALSO PROVIDES VERY GOOD PROTECTION AGAINST CORROSION.

APPLICATION

READY MIX IS RECOMMENDED FOR USE IN APPLICATIONS REQUIRING BS6580-1992 QUALITY STANDARD. READY MIX SHOULD NOT BE MIXED WITH OTHER ENGINE COOLANTS. MOST COOLANT BLENDS ARE BASED ON CAREFULLY BALANCED MIXTURES OF VARIOUS CORROSION INHIBITORS.

MIXING OF COOLANTS WITH DIFFERENT INHIBITOR PACKAGES CAN LEAD TO LOSS OF CORROSION PROTECTION.

SPECIFICATION OF READY MIX -36°C

READY MIX -36°C	
COLOR	FLUORESCENT GREEN
DENSITY AT 20°C, G/CM3	1.08
BOILING POINT, °C	>110
FLASH POINT, °C	> 115
PH VALUE	7.5
RESERVE ALKALINITY (M/10HCL), ML	10

THESE CHARACTERISTICS ARE TYPICAL OF CURRENT PRODUCTION.
WHILST FUTURE PRODUCTION WILL CONFORM TO KINSLEE SPECIFICATION, VARIATIONS IN THESE CHARACTERISTICS MAY OCCUR.